

# Gas Radiant Broilers

Models  MVRB60

MVRB90

MVRB120



MVRB60 on Stand

## Standard Features

- Counter top mounted model
- Adjustable height branding plate
- Scraper for cleaning branding plates
- Low turn down facility on all burners
- Variable heat zones
- Drainage channel and large capacity fat collection drawer
- Piezo ignition

## Options & Accessories

- Open Stand mounted on legs or castors giving a working height of 900mm
- Flexible gas hose
- Also available in Natural Gas or Propane

## Specifications

Moorwood Vulcan offers the ultimate in design and service excellence with this stylish, functional selection of medium duty prime cooking equipment, manufactured to the highest standards.

The Moorwood Vulcan Radiant Broiler is available in 600mm, 900mm and 1200mm versions, giving options for all establishments large or small, from the high-class restaurant to the small café. A flexible range of temperatures is provided by the fully adjustable burners and variable height grill bars. Easy and safe lighting is achieved by incorporating the piezo ignition. Providing perfect and succulent results for any product suitable for chargrill cooking.

The product is ideal for a hard working kitchen and is designed to provide many years of value-for money service.

Suites with other Moorwood Vulcan products to make a modular cooking centre



ENODIS UK FOOD SERVICE

5E Langley Business Park, Station Road, Langley, Berkshire SL3 8DS  
Fax: 01753 485901 Email: [info@enodis.com](mailto:info@enodis.com)

Group Tel: 0845 370 4888


[www.enodisuk.com](http://www.enodisuk.com)

Datasheet Part No. 933155-01



Revision No. 1

August 2008








**MVRB60**



**MVRB90**



**MVRB120**



**DIMENSIONS**

MODEL NO.	OVERALL SIZE			COOKING SURFACE		NET WEIGHT	SHIPPING WEIGHT (APPROX)
	HEIGHT	WIDTH	DEPTH	WIDTH	DEPTH		
<b>MVRB60</b>	445mm	600mm	710mm	572mm	525mm	46kg	55kg
<b>MVRB90</b>	445mm	900mm	710mm	858mm	525mm	85kg	96kg
<b>MVRB120</b>	445mm	1200mm	710mm	1144mm	525mm	95kg	110kg

**POWER REQUIREMENTS**

Model NO.	Gas Consumption per hr. Natural Gas	Gas Consumption per hr. Propane Gas	Gas Connection	Total Output (kW) NG / LP
<b>MVRB60</b>	1.68m <sup>3</sup> /hr	1.17kg/hr	R 3/4"	16.8 / 16.6
<b>MVRB90</b>	2.52m <sup>3</sup> /hr	1.8kg/hr	R 3/4"	25.2 / 24.9
<b>MVRB120</b>	3.4m <sup>3</sup> /hr	2.3kg/hr	R 3/4"	33.6 / 33.1

If using a flexible snap on connection hose, a 3/4" diameter is required. Please consult the Technical Manual or CORGI regulations for further details. Please allow adequate clearance for Connection elbow & governor arrangement behind equipment

For further information on MV products and services or advice on which unit suits you best please contact the sales department.

**ENODIS UK FOOD SERVICE**

5E Langley Business Park, Station Road, Langley, Berkshire SL3 8DS  
 Fax: 01753 485901 Email: info@enodis.com

Group Tel: 0845 370 4888

www.enodisuk.com

Datasheet Part No. 933155-01

Revision No. 1

August 2008

